

Hyosung 9I

Elevate the branch experience with the industry's most efficient cash recycler.

The Hyosung 9I island drive-up ATM revolutionizes digital branch transformation with state-of-the-art engineering and a wide range of self-service capabilities powered by our industry-leading BlueVerse™ software.

Feature Highlights

Advanced Cash Recycling

Reduce operating costs and increase availability

Innovative Modular Design

Maximize ATM availability and serviceability

Flexible Configurations

Choose modules that best meet your needs

Full Denomination Support

with split cassette option



Modular Design



19" Touchscreen



Recycle up to 8 denominations



100 notes per transaction



Up to 3,440 note capacity per cassette

Specifications

Dimensions

- Height: 58.6" (1,488mm)
- Width: 42.9" (1,089mm)
- Depth: 39.4" (1,000mm)
- Weight: 2,361.2 lbs (1,071 kg)

Environmental Conditions

- Temperature: 32°F ~ 104°F (0°C ~ 40°C)
Exterior with heater/AC: -31°F ~ 122°F (-35°C ~ 50°C)
- Humidity 25% ~ 85%

System Platform

- Microsoft Windows® Platform
- Hyosung BlueVerse™

Customer Interface

- 19" Landscape LCD Sunlight Viewable Touchscreen
- Card Reader
- NFC Reader
- Audio Jack

Servicing

- Front Access
- State of health indicators for all modules

Media Handling

- Recycling/Deposit Module (Presenter Cash Tray)
 - Configurable with up to 4 large recycling cassettes or 8 small recycling cassettes, plus 1 deposit cassette
 - Large Cassette: 3,440 notes¹
 - Split Cassette: Top 800 notes¹
Bottom 1,480 notes¹
 - Deposit Cassette²: 3,400 notes¹
 - Retract Cassette: 200 notes¹
 - Bundle up to 100 notes per withdrawal/ deposit transaction
- Check Acceptor
 - Up to 30 checks per transaction
 - Deposit cassette: 1,000 checks
 - Retract bin: 50 checks
 - OCR E13B/CMC7 capable

Security

- Safe – CEN3 ExGas
- Cencon Lock
- Alarm (Seismic & heat)
- Security Camera (IP or CCD optional)

Printer

- 3.1" graphical thermal receipt printer

Power Supply

- AC 100 ~ 127V ± 10% / 10.0A, 50 ~ 60 Hz

Additional Features

- Lead-through indicator
- Speaker
- Communication – TCP/IP
- Fitness sorting
- Multi-channel communications
- ActiveTeller capable
- Battery backup built in
- Barcode reader
- Palm vein reader (optional)
- ID scanner (optional)
- Heater

Footnotes:

1: Subject to media quality and other variables

2: Deposit cassette configurations:

- 1 Slot: 3,400 notes¹
- 2 Slots: 500 notes / 2,600 notes¹
- 3 Slots: 500 notes / 500 notes / 1,800 notes¹

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

