



## Hyosung is Moving at the Speed of Retail.

Hyosung is proud to introduce the latest addition to the retail family – the MX5200SE. The MX5200SE delivers maximum service and security for retail locations with large transaction revenue potential, combining the usability and maintainability of a retail ATM with the advanced functions and security of a financial institution cash dispenser.

### Features

#### Innovation

The striking design and advanced function options of the MX5200SE make this ATM the ideal choice for bank branded, high–end retail locations and sites requiring greater security. The MX5200SE offers a brilliant 12.1–inch TFT LCD monitor with a function key or a touch/function key user interface (Microsoft Windows<sup>®</sup> CE 6.0).

#### Reliability

The MX5200SE can be counted on to stand up to heavy use. The system utilizes Hyosung modular component architecture designed for high reliability, quick and easy service, and accessibility.

#### Capacity

The MX5200SE cash capacity ranges from a single 2,000–note cassette to three 2,000–note cassettes, providing a maximum load of 6,000 notes. Using proven Hyosung dispenser technology, the MX5200SE is the ideal platform for high transaction volume sites.

#### **Security Options**

Security is essential with any ATM and especially for cash dispensers with a large cash capacity. The MX5200SE offers customers a choice of a UL 291 certified business hours safe with enhanced break-in protection or a heavy-duty Level-1 safe. Enhanced physical protection includes a reinforced cash tray and heavier metal plating. For added intrusion and fraud security, the MX5200SE offers a camera-ready fascia, optional anti-skim EMV card reader and support for Transport Layer Security (TLS) network encryption protocol.







For more information visit hyosunginnovue.com



# 5200SE

## **Standard Features**

#### **Dimensions (UL291 base)**

- Height: 1406 mm (55.4")
- Width: 410 mm (16.1")
- Depth: 616.3 mm (24.3")
- Weight: 275.5 kg (607.37 lbs)

#### **Environmental Conditions**

- Temperature: 32°F ~ 104°F (0°C ~ 40°C)
- Humidity: 20% ~ 85%

#### **System Platform**

• Microsoft Windows® CE 7.0

#### **Customer Interface**

- 12.1" TFT LCD
- EMV Dip Type card reader
- Card Reader Anti-skimming (optional)
- Function key/touch

#### **Media Handling**

- 1,000 note removable cassette\*
- 2,000 note removable cassette\*
- Upgradable to 3 cassettes (maximum 6,000 notes)

#### Security

- Safe UL291 business hours Level 1 safe (optional)
- Electronic lock
- Cencon or S&G (optional)

#### Printer

- Thermal line 3" receipt printer
- Electronic journal

#### **Power Supply**

• AC 110-240, V, 50-60 Hz

#### **Additional Features**

- Communication TCP/IP
- Lead Through indicator
- Earphone jack
- NFC reader (optional)
- Digital receipt
- Supports 6 Languages: English, Spanish, French, Japanese, Chinese, & Korean
- Enhanced Standard 1 Emulation
- Dynamic currency conversion (DCC)
- Donations transaction
- Decimal point percentage surcharge
- TLS protocol communication

\*Subject to note quality and other variables

Note: Internal components may change with the introduction of new technology. Hyosung reserves the right to change the specifications of this ATM to accommodate the changes in technology.

